

Part No.	Capacity	Throat Depth	Clamping Pressure	Pads	Rail Size	Tapped Hole	Weight
UD45-C3 (UD45M-C3)	4-1/2" (114 mm)	3-1/4" (83 mm)	500 LBS (227 kg)	Standard	5/8 x 5/16" (16 x 8 mm)	5/16-18 (M8)	1.3 LBS (0.6 kg)
UD65-C3 (UD65M-C3)	6-1/2" (165 mm)	3-1/4" (83 mm)	500 LBS (227 kg)	Standard	5/8 x 5/16" (16 x 8 mm)	5/16-18 (M8)	1.6 LBS (0.7 kg)
UF65-C3 (UF65M-C3)	6-1/2" (165 mm)	4-3/4" (120 mm)	1,000 LBS (454 kg)	Standard	7/8 x 7/16" (22 x 11 mm)	3/8-16 (M10)	2.9 LBS (1.3 kg)
UG85-C3 (UG85M-C3)	8-1/2" (216 mm)	4-3/4" (120 mm)	1,200 LBS (544 kg)	Standard	1 x 15/32" (25 x 12 mm)	3/8-16 (M10)	4.1 LBS (1.9 kg)
UG125-C3 (UG125M-C3)	12-1/2" (318 mm)	4-3/4" (120 mm)	1,200 LBS (544 kg)	Standard	1 x 15/32" (25 x 12 mm)	3/8-16 (M10)	4.5 LBS (2.1 kg)
UG1257-C3 (UG1257M-C3)	12-1/2" (318 mm)	7" *Deep Throat (180 mm)	800 LBS (363 kg)	Standard	1 x 15/32" (25 x 12 mm)	3/8-16 (M10)	6.5 LBS (2.9 kg)