



INQUIRE ABOUT THIS PRODUCT

BUY NOW

ST2600 TORCH

[OVERVIEW](#)

[DOCUMENTS AND SPECS](#)

[ORDERING INFORMATION](#)



Documents

Specifications	
Cutting Range	3.2-203.2 mm (1/8-8 in.)
Head Angle	90 degrees
Model	SST 2600FC
Valve Position	Top Rear
Cutting Range	3.2-203.2 mm (1/8-8 in.)
Head Angle	75 degrees

Model	SST 2601FC
Valve Position	Top Rear
Cutting Range	3.2-203.2 mm (1/8-8 in.)
Head Angle	90 degrees
Model	ST 2600FC
Valve Position	Top Rear
Cutting Range	3.2-203.2 mm (1/8-8 in.)
Head Angle	75 degrees
Model	ST 2601FC
Valve Position	Top Rear
Cutting Range	3.2-203.2 mm (1/8-8 in.)
Head Angle	75 degrees
Model	ST 2601FCL
Valve Position	Top Rear
Cutting Range	3.2-203.2 mm (1/8-8 in.)
Head Angle	180 degrees
Model	ST 2602FC
Valve Position	Top Rear
Cutting Range	3.2-203.2 mm (1/8-8 in.)
Head Angle	75 degrees
Model	ST 2611FC
Valve Position	Top Rear
Cutting Range	3.2-203.2 mm (1/8-8 in.)
Head Angle	90 degrees
Model	ST 2630FC
Valve Position	Top Rear
Cutting Range	3.2-203.2 mm (1/8-8 in.)
Head Angle	75 degrees
Model	ST 2631FC
Valve Position	Top Rear
Cutting Range	3.2-203.2 mm (1/8-8 in.)
Head Angle	180 degrees
Model	ST 2632FC
Valve Position	Top Rear

Cutting Range	3.2-203.2 mm (1/8-8 in.)
Head Angle	75 degrees
Model	ST 2651FC
Valve Position	Top Rear
Cutting Range	3.2-203.2 mm (1/8-8 in.)
Head Angle	180 degrees
Model	ST 2652FC
Valve Position	Top Rear
Cutting Range	3.2-203.2 mm (1/8-8 in.)
Head Angle	90 degrees
Model	ST 2670FC
Valve Position	Top Rear
Cutting Range	3.2-203.2 mm (1/8-8 in.)
Head Angle	75 degrees
Model	ST 2671FC
Valve Position	Top Rear
Cutting Range	3.2-203.2 mm (1/8-8 in.)
Head Angle	180 degrees
Model	ST 2672FC
Valve Position	Top Rear

<https://plus.google.com/115697060530124940386>