



VICTOR
AN ESAB® BRAND

INQUIRE ABOUT THIS PRODUCT

BUY NOW

SR 310 SERIES FLOW METER

[OVERVIEW](#)

[DOCUMENTS AND SPECS](#)

[ORDERING INFORMATION](#)



The SR311-320 CO2 Flowmeter adjustable pressure gauge is specifically designed for use with standard (non-siphoned) carbon dioxide cylinders. Our unique design incorporates aluminum heat sink fins which permit high flow rates without freeze-up.

Features

Designed for CO2 application (non-siphoned tube cylinders)

High flow CO2 applications (SR 310 100 PSIG) (SR 311/312 100 SCFH) with adequate supply or source

Designed for core wire applications

Machined aluminum body & housing cap

2" (50.8 mm) gauge

Stem type seat mechanism

1.75" (44.5 mm) diaphragm - fabric reinforced neoprene

Self reseating relief valve (not designed to protect downstream equipment)

Sintered inlet filter - bronze

A regulator equipped with a flow gauge is not accurate when a back pressure in excess of 2 PSIG exists at the outlet. Back pressure is caused by a restriction in the equipment downstream of the flow gauge. Metering valves, kinked hoses or even very long hoses are restrictions that can cause back pressure. In applications where back pressure in excess of 2 PSIG can be expected, a regulator equipped with a flow meter should be used. **WARNING:** High gas withdrawal rates may cause regulator freeze up and will require cylinder manifolding. Consult your gas supplier

Industries

Industrial and General Fabrication

Structural Steel Fabrication

Repair and Maintenance

Light Fabrication